


SPRĘŻARKI PÓLHERMETYCZNE

Typ	Cena	Olej estrowy	Grzałka	Presostat oleju FD113ZU	Regulacja wydajności: głowica/zawór CR	Wydajność w [W] dla R 404A Temperatura skraplania 40°C			V _{th}	Ilość oleju SEZ 32	Przyłącza ssawne / tłoczne
						Wyposażenie					
	EUR	EUR	EUR	EUR	EUR	0	-5	-25	m ³ /h	litr	mm
2KES-05Y	713	S	31	-	-	2 920	2 390	900	4,06	1,00	16/12
2JES-07Y	721	S	31	-	-	3 950	3 250	1 290	5,21	1,00	16/12
2HES-1Y	728	S	31	-	-	4 950	4 090	1 650	6,51	1,00	16/12
2HES-2Y	743	S	31	-	-	5 060	4 190	1 700	6,51	1,00	16/12
2GES-2Y	743	S	31	-	-	5 780	4 790	1 990	7,58	1,00	16/12
2FES-2Y	776	S	31	-	-	7190	5 960	2 450	9,54	1,00	16/12
2FES-3Y	814	S	31	-	-	7 160	5 930	2 440	9,54	1,00	16/12
2EES-2Y	1088	S	37	-	-	9 250	7 670	3 180	11,40	1,50	22/16
2EES-3Y	1176	S	37	-	-	9 250	7 670	3 180	11,40	1,50	22/16
2DES-2Y	1133	S	37	-	-	11 040	9 170	3 850	13,40	1,50	22/16
2DES-3Y	1182	S	37	-	-	11 040	9 170	3 850	13,40	1,50	22/16
2CES-3Y	1176	S	37	-	-	13 550	11 280	4 830	16,20	1,50	22/16
2CES-4Y	1229	S	37	-	-	13 550	11 280	4 830	16,20	1,50	22/16
4FES-3Y	1279	S	37	-	46/140	14 840	12 260	5 140	18,10	2,00	22/16
4FES-5Y	1416	S	37	-	46/140	14 830	12 260	5 140	18,10	2,00	22/16
4EES-4Y	1311	S	37	-	46/140	18 810	15 550	6 520	22,70	2,00	28/16
4EES-6Y	1508	S	37	-	46/140	18 650	15 390	6 380	22,70	2,00	28/16
4DES-5Y	1656	S	37	-	46/140	22 400	18 530	7 790	26,80	2,00	28/22
4DES-7Y	1743	S	37	-	46/140	22 400	18 540	7 790	26,80	2,00	28/22
4CES-6Y	1823	S	37	-	46/140	27 150	22 400	9 310	32,50	2,00	28/22
4CES-9Y	1895	S	37	-	46/140	27 150	22 400	9 310	32,50	2,00	28/22
4VES-7Y	2386	S	37	-	46/140	28 800	23 650	9 350	34,70	2,60	28/22
4VES-10Y	2484	S	37	-	46/140	28 800	23 650	9 350	34,70	2,60	28/22
4TES-9Y	2450	S	37	-	46/140	34 700	28 600	11 580	41,30	2,60	35/28
4TES-12Y	2559	S	37	-	46/140	34 700	28 550	11 500	41,30	2,60	35/28
4PES-12Y	2662	S	37	-	46/140	40 000	32 800	12 860	48,50	2,60	35/28
4PES-15Y	2779	S	37	-	46/140	39 800	32 600	12 710	48,50	2,60	42/28
4NES-14Y	3002	S	37	-	46/140	47 200	38 800	15 640	56,20	2,60	35/28
4NES-20Y	3188	S	37	-	46/140	47 200	38 800	15 660	56,20	2,60	42/28


SPRĘŻARKI PÓLHERMETYCZNE

Typ	Cena	Olej estrowy	Grzałka	Presostat oleju FD113ZU	Regulacja wydajności: głowicazawór CR	Wydajność w [W] dla R 404A Temperatura skraplania 40°C			Vth	Ilość oleju SEZ 32	Przyłącza ssawne / tłoczne
						Wyposażenie					
	EUR	EUR	EUR	EUR	EUR	0	-5	-25	m ³ /h	litr	mm
4JE-15Y	3946	S	42	120	46/141	53 400	44 300	18 600	63,50	4,00	42/28
4JE-22Y	4151	S	42	120	46/141	52 500	43 400	17 780	63,50	4,00	42/28
4HE-18Y	3955	S	42	120	46/141	62 200	51 700	22 050	73,70	4,00	42/28
4HE-25Y	4162	S	42	120	46/141	61 500	51 000	21 400	73,70	4,00	54/28
4GE-23Y	4442	S	42	120	46/141	71 800	59 800	25 900	84,60	4,50	54/28
4GE-30Y	4629	S	42	120	46/141	70 600	58 600	24 800	84,60	4,50	54/28
4FE-28Y	4609	S	42	120	46/141	85 000	71 000	31 100	101,80	4,50	54/28
4FE-35Y	4801	S	42	120	46/141	84 500	70 500	30 650	101,80	4,50	54/28
6JE-25Y	4884	S	42	120	46/141	79 400	65 900	27 700	95,30	4,75	54/35
6JE-33Y	5619	S	42	120	46/141	77 800	64 200	26 200	95,30	4,75	54/35
6HE-28Y	5035	S	42	120	46/141	91 300	75 900	32 450	110,50	4,75	54/35
6HE-35Y	5781	S	42	120	46/141	90 300	74 900	31 500	110,50	4,75	54/35
6GE-34Y	5781	S	42	120	46/141	105 200	87 900	38 900	126,80	4,75	54/35
6GE-40Y	6177	S	42	120	46/141	102 400	85 200	36 400	126,80	4,75	54/35
6FE-44Y	7014	S	42	120	46/141	126 600	105 700	46 350	151,60	4,75	54/42
6FE-50Y	7204	S	42	120	46/141	124 600	103 800	44 600	151,60	4,75	54/42
8GE-60Y	8822	S	42	120	46/141	145 400	121 200	51 300	185,00	5,00	76/42
8FE-70Y	9584	S	42	120	46/141	172 100	143 500	60 800	221,00	5,00	76/54