


**GEA Bock**
**AGREGATY**

Typ	Cena	Olej estrowy	Gizalka	Presostat oleju FD113ZU	Regulacja wydajności: głowica/zawór CR	Wydajność w [W] dla R 404A Temperatura otoczenia 27°C			Wentylatory skrapi. 220V Ilość x pobór prądu	Przyłącza ssawne /płynowe
						Wypozażenie				
	EUR	EUR	EUR	EUR	EUR	0	-8	-28	szt x A	mm
SHGX 12P/60-4SL	1485	S	34	120*	-	4 350	3 150	1 300	1 x 1,25	16 / 10
SHGX 12P/75-4L	1485	S	34	120*	-		3 900	1 700	1 x 1,25	16 / 10
SHGX 12P/75-4SL	1501	S	34	120*	-	5 500	4 050	1 750	1 x 1,25	16 / 10
SHGX 12P/90-4L	1565	S	34	120*	-		4 650	2 050	1 x 1,25	16 / 10
SHGX 12P/90-4SL	1602	S	34	120*	-	5 970	4 800	2 150	1 x 1,25	16 / 10
SHGX 12P/110-4L	1602	S	34	120*	-		5 400	2 500	1 x 1,25	16 / 10
SHGX 12P/110-4SL	1708	S	34	120*	-	7 300	5 500	2 500	1 x 1,25	16 / 10
SHGX 22P/125-4L	1713	S	34	120*	-		6 050	2 700	1 x 1,25	22 / 12
SHGX 22P/125-4SL	1861	S	34	120*	-	8 400	6 400	2 750	1 x 1,25	22 / 12
SHGX 22P/160-4L	1821	S	34	120*	-		7 550	3 300	1 x 1,25	22 / 12
SHGX 22P/160-4SL	1867	S	34	120*	-	10 200	7 550	3 300	1 x 1,25	22 / 12
SHGX 22P/190-4L	2008	S	34	120*	-		9 700	4 200	1 x 2,80	22 / 12
SHGX 22P/190-4SL	2058	S	34	120*	-	13 150	9 700	4 200	1 x 2,80	22 / 12
SHGX 34P/215-4L *	2155	S	34	120*	29/195		10 750	4 700	1 x 2,80	22 / 12
SHGX 34P/215-4SL *	2416	S	34	120*	29/195	14 400	10 750	4 700	1 x 2,80	22 / 16
SHGX 34P/255-4L *	2183	S	34	120*	29/195		12 150	5 400	1 x 2,80	28 / 12
SHGX 34P/255-4SL *	2504	S	34	120*	29/195	16 200	12 150	5 400	1 x 2,80	28 / 16
SHGX 34P/315-4L *	2457	S	34	120*	29/195		14 200	6 500	1 x 2,80	28 / 12
SHGX 34P/315-4SL *	2922	S	34	120*	29/195	20 050	15 050	6 700	2 x 2,80	28 / 16
SHGX 34P/380-4L *	3048	S	34	120*	29/195		17 350	7 900	2 x 2,80	28 / 16
SHGX 34P/380-4SL *	3269	S	34	120*	29/195	24 400	18 300	8 100	2 x 2,80	28 / 16
SHGX 4/465-4L	3642	S	38	120	0/195		22 900	10 650	2 x 2,80	35 / 16
SHGX 4/465-4SL	4341	S	38	120	0/195	34 250	25 700	11 350	4 x 2,80	35 / 16
SHGX 4/555-4L	3735	S	38	120	0/195		25 700	12 250	4 x 2,80	35 / 16
SHGX 4/555-4SL	5192	S	38	120	0/195	39 750	29 950	13 350	4 x 2,80	35 / 22
SHGX 4/650-4L	4745	S	38	120	0/195		33 200	15 200	4 x 2,80	42 / 22
SHGX 4/650-4SL	5496	S	38	120	0/195	44 650	33 850	15 350	4 x 2,80	42 / 22

Sprężarki HGX 34P oznaczone (\*) będą stopniowo zastępowane przez sprężarki HGX 34e.

Producent nie wymaga w tych sprężarkach presostatu olejowego, ale umożliwia jego zastosowanie